

Effective date: Mar 1, 2002

# Isopar™ H

Isoparaffin

## Product Properties

Property	Units	Typical values	Test method
Distillation range	°C		ASTM D 86
IBP		179	
DP		187	
Flash point	°C	53	ASTM D 56
Density @ 15 °C	kg/dm <sup>3</sup>	0.759	ASTM D 4052
Viscosity @ 25 °C	mm <sup>2</sup> /s	1.80	ASTM D 445
Evaporation rate (n-BuAc=100)	-	11	ASTM D 3539
KB value	-	26	ASTM D 1133
Aniline point	°C	85	ASTM D 611
Aromatic content	wt%	< 0.01	AM-S 140.31
Colour (Saybolt)	-	+ 30	ASTM D 156
Bromine index	mg/100g	< 5	ASTM D 2710
Surface tension @ 25 °C	mN/m	23	ASTM D 1331
Refractive index @ 20 °C	-	1.421	ASTM D 1218

### Notes

- Values indicated describe typical physical properties and do not constitute specification limits.
- This product typically contains less than 10 ppm Benzene and less than 5 ppm sulphur.

ExxonMobil's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. ExxonMobil reserves the right to use other equivalent test methods in certifying this product.

© 2000 ExxonMobil. The user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to a Web site. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no warranty against patent infringement, nor any endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward.